

PRODUCT-DETAILS

ACQ580-01-10A6-2+P918

LV AC wall-mounted drive for water and wastewater, 208 ... 240 V (ACQ580-01-10A6-2+P918)



General Information	
Global Commercial Alias	ACQ580-01-10A6-2+P918
Product ID	3AXD50000268436
ABB Type Designation	ACQ580-01-10A6-2+P918
EAN	6438177537380
Catalog Description	LV AC wall-mounted drive for water and wastewater, 208 ... 240 V (ACQ580-01-10A6-2+P918)
Long Description	<p>The ACQ580-01 drives deliver innovative pump features for the water and wastewater industry, securing energy efficient flow of water and wastewater in your pumping solutions. This robust and compact wall-mounted drive has built-in pump application functionality such as sensorless flow calculation, multipump control, level control, soft pipe fill, dry run protection, quick ramps and a solution for keeping the impeller of the pump clean. Usability is further enhanced with the intuitive Hand-Off-Auto control panel, the PC tool Drive composer and an optional Bluetooth® control panel. The built-in energy calculator visualizes the energy savings achieved with the use of the drive. The ACQ580-01 variant comes in IP21 enclosure as standard and can be installed on the wall. Also, IP55 and flange mounting units are available.</p>

Ordering	
Country of Origin	United States (US) China (CN)
Customs Tariff Number	85044084
Made To Order	No

Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	10.1 lb
Product Net Depth / Length	8.78 in
Product Net Height	14.69 in
Product Net Width	4.82 in
Package Level 1 Units	1 carton

Technical

Number of Phases	3
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Frequency (f)	50/60 Hz
Frame Size	R1
Input Voltage (U _{in})	208 ... 240 V
Mounting Type	Wall-mounting
Apparent Power Output	4.2 kV·A
Efficiency Level	IE2
Standby Loss	13 W

Complete Drive Module
Efficiency (61800-9-2)

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	49 W	1.2 %	82.1 %
0 / 50 %	58 W	1.4 %	88.2 %
0 / 100 %	81 W	1.9 %	90.8 %
50 / 25 %	51 W	1.2 %	90.1 %
50 / 50 %	63 W	1.5 %	93.5 %
50 / 100 %	94 W	2.2 %	94.7 %
90 / 50 %	72 W	1.7 %	95.7 %
90 / 100 %	120 W	2.8 %	96.2 %

Temperature Rating	Maximum 40 °C
--------------------	---------------

Additional Information

Product Name	AC Drive
--------------	----------

Classifications

UNSPSC	39122001
--------	----------

Environmental	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories
Drives → Low Voltage AC Drives → Industry-Specific Drives → Drives for water → ACQ580-01 - Wall-mounted drive for water and wastewater

