



PRODUCT-DETAILS

3GAA062311-CSF

IE2 High Efficiency Aluminum Motors, 0.12 kW,
400 V (3GAA062311-CSF)



General Information

Product ID	3GAA062311-CSF
ABB Type Designation	M3AA 63A 4
Catalog Description	IE2 High Efficiency Aluminum Motors, 0.12 kW, 400 V (3GAA062311-CSF)

Ordering

ABB Type Designation	M3AA 63A 4
Invoice Description	M3AA 63A 4
Product Name	3-Phase squirrel cage motor
Product Type	3AA2_M3AA_IE2_AA
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	China (CN)
Customs Tariff Number	85015100
Replaced Product ID (OLD)	3GAA062001-CSE 3GAA062311-CSC 3GAA062001-CSC 3GAA062311-CSE
Stocked At (Warehouses)	Menden, Germany Sant Quirze del Vallés - BCN, Spain Vittuone, Italy

Medium Description	0.12kW, 4 Poles, Frame Size 63, 3 Phases, 400V, 50Hz, IP55 Enclosure,
--------------------	---

	IMB14/IM3601 Mounting (3GAA062311-CSF)
Short Description	0.12kW, 4P, Frame Size 63, 3PH, 400V, 50Hz, IP55, IMB14/IM3601

Electrical

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.12 kW	1403 r/min	0.41 A	0.630	59.10 %	0.82 N·m	2.90
D	--	50 Hz	230 V	0.12 kW	1403 r/min	0.71 A	0.630	59.10 %	0.82 N·m	2.90
Y	--	60 Hz	460 V	0.12 kW	1724 r/min	0.38 A	0.600	64.00 %	0.66 N·m	3.30

Connection Configuration	Y
Temperature Class Default	--
Input Voltage (U _{in})	400 V
Frequency (f)	50 Hz
Output Power	0.12 kW
Altitude	1000 m
Ambient Temperature	40 °C
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 59.1 % Partial Load (75%) 55.8 % Partial Load (50%) 47.1 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 64.0 % Partial Load (75%) 59.7 % Partial Load (50%) 51.0 %
IP Class	IP55
Insulation Class	ICLF
Direction of Rotation	Both sides
Number of Poles (High)	4
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S

Mechanical

Frame Material	Aluminum
Frame Size	63
Bearing	6201-2Z/C3
Bearing NDE	6201-2Z/C3
IM Class	IMB14 IM3601
Terminator Box Location	D-End top

Dimensions

Package Level 1 Units	0 carton
Product Net Depth / Length	208 mm
Product Net Height	154 mm
Product Net Width	124 mm
Product Net Weight	3.7 kg
Gross Weight	4.7 kg

Environmental

WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)

Classifications

UNSPSC 26101100

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

