




PRODUCT-DETAILS

3GAA073003-CSE

IE2 High Efficiency Aluminum Motors, 0.37 kW,  
400 V (3GAA073003-CSE)



General Information

Product ID	3GAA073003-CSE
ABB Type Designation	M3AA 71C 6 HO
Catalog Description	IE2 High Efficiency Aluminum Motors, 0.37 kW, 400 V (3GAA073003-CSE)

Ordering

ABB Type Designation	M3AA 71C 6 HO
Invoice Description	M3AA 71C 6 0,32KW 6P 380VY 50HZ B14
Product Name	3-Phase squirrel cage motor
Product Type	3AA2_M3AA_IE2_AA
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	Romania (RO) Turkiye (TR)
Customs Tariff Number	85015100
Stocked At (Warehouses)	Menden, Germany Vittuone, Italy
Medium Description	0.37kW, 6 Poles, Frame Size 71, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB14/IM3601 Mounting (3GAA073003-CSE)
Short Description	0.37kW, 6P, Frame Size 71, 3PH, 400V, 50Hz, IP55, IMB14/IM3601

Electrical

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.37 kW	895 r/min	1.27 A	0.660	63.60 %	3.90 N·m	3.70
D	--	50 Hz	230 V	0.37 kW	895 r/min	2.20 A	0.660	63.60 %	3.90 N·m	3.70
Y	--	60 Hz	460 V	0.37 kW	1115 r/min	1.11 A	0.610	68.10 %	3.10 N·m	4.50
Connection Configuration										Y
Temperature Class Default										--
Input Voltage (U <sub>in</sub> )										400 V
Frequency (f)										50 Hz
Output Power										0.37 kW
Altitude										1000 m
Ambient Temperature										40 °C
IC Class										IC411
IE Class Data (50 Hz)										IE Class IE1 Full Load (100%) 63.6 % Partial Load (75%) 64.1 % Partial Load (50%) 59.3 %
IE Class Data (60 Hz)										IE Class IE2 Full Load (100%) 68.1 % Partial Load (75%) 66.3 % Partial Load (50%) 60.4 %
IP Class										IP55
Insulation Class										ICLF
Direction of Rotation										Both sides
Number of Poles (High)										6
Two Speed Motor										No
Type of Duty										S1
Voltage Code										S

Mechanical

Frame Material	Aluminum
Frame Size	71
Bearing	6202-2Z C3
Bearing NDE	6202-2Z C3
Lubrication	For life
IM Class	IMB14 IM3601
Terminator Box Location	Top

Dimensions

Package Level 1 Units	0 carton
Product Net Depth / Length	239.5 mm
Product Net Height	180 mm
Product Net Width	136 mm
Product Net Weight	7 kg
Gross Weight	10 kg

Environmental

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)

Classifications	
Standards	IEC 60034-1
UNSPSC	26101100

Categories
Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

