




PRODUCT-DETAILS

# 3GAA092530-CPK

## IE3 Premium Efficiency Aluminum Motors, 1.1 kW, 230 V (3GAA092530-CPK)



General Information	
Product ID	3GAA092530-CPK
ABB Type Designation	M3AA 90LC 4
Catalog Description	IE3 Premium Efficiency Aluminum Motors, 1.1 kW, 230 V (3GAA092530-CPK)

Ordering	
ABB Type Designation	M3AA 90LC 4
Invoice Description	M3AA 90LC 4
Product Name	3-Phase squirrel cage motor
Product Type	3AA3_M3AA_IE3_AA
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Medium Description	1.1kW, 4 Poles, Frame Size 90, 3 Phases, 230V, 60Hz, IP55 Enclosure, IMB14/IM3601 Mounting (3GAA092530-CPK)
Short Description	1.1kW, 4P, Frame Size 90, 3PH, 230V, 60Hz, IP55, IMB14/IM3601

Electrical											
Electrical Data											
Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN	
D	--	50 Hz	200 V	1.10 kW	1442 r/min	4.60 A	0.800	85.60 %	7.20 N·m	7.90	
D	--	60 Hz	230 V	1.10 kW	1749 r/min	4.10 A	0.770	86.50 %	6.00 N·m	8.40	
Connection Configuration											D
Temperature Class Default											--
Input Voltage (U <sub>in</sub> )											230 V
Frequency (f)											60 Hz
Output Power											1.1 kW
Altitude											1000 m
Ambient Temperature											40 °C
IC Class											IC411
IE Class Data (50 Hz)											IE Class IE3 Full Load (100%) 85.6 % Partial Load (75%) 85.1 % Partial Load (50%) 83.4 %
IE Class Data (60 Hz)											IE Class IE3 Full Load (100%) 86.5 % Partial Load (75%) 85.4 % Partial Load (50%) 82.5 %
IP Class											IP55
Insulation Class											ICLF
Direction of Rotation											Both sides
Number of Poles (High)											4
Two Speed Motor											No
Type of Duty											S1
Voltage Code											P
Mechanical											
Frame Material											Aluminum
Frame Size											90
Bearing											6205-2Z/C3
Bearing NDE											6204-2Z/C3
IM Class											IMB14 IM3601
Terminator Box Location											D-End top
Dimensions											
Package Level 1 Units											0 carton
Product Net Depth / Length											331.5 mm
Product Net Height											217 mm
Product Net Width											170 mm
Product Net Weight											19 kg
Gross Weight											22 kg

Environmental	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)

Classifications	
UNSPSC	26101100

Categories	
Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors	

