




PRODUCT-DETAILS

3GAA131130-CDE

IE2 High Efficiency Aluminum Motors, 7.5 kW, 400 V (3GAA131130-CDE)



General Information

Product ID	3GAA131130-CDE
ABB Type Designation	M3AA 132SC 2
Catalog Description	IE2 High Efficiency Aluminum Motors, 7.5 kW, 400 V (3GAA131130-CDE)

Ordering

ABB Type Designation	M3AA 132SC 2
Invoice Description	M3AA 132SC 2
Product Name	3-Phase squirrel cage motor
Product Type	3AA2_M3AA_IE2_AA
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015220
Replaced Product ID (OLD)	3GAA1311313-CDE
Stocked At (Warehouses)	Shanghai, China
Medium Description	7.5kW, 2 Poles, Frame Size 132, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB14/IM3601 Mounting (3GAA131130-CDE)

Short Description7.5kW, 2P, Frame Size 132, 3PH, 400V, 50Hz, IP55, IMB14/IM3601

Electrical

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	7.50 kW	2915 r/min	7.92 A	0.880	88.50 %	24.50 N·m	7.60
D	--	50 Hz	400 V	7.50 kW	2915 r/min	13.60 A	0.880	88.50 %	24.50 N·m	7.60
D	--	60 Hz	460 V	7.50 kW	3525 r/min	12.00 A	0.890	89.50 %	20.30 N·m	8.70

Connection Configuration	D
Temperature Class Default	--
Input Voltage (U _{in})	400 V
Frequency (f)	50 Hz
Output Power	7.5 kW
Altitude	1000 m
Ambient Temperature	40 °C
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 88.5 % Partial Load (75%) 89.2 % Partial Load (50%) 88.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 89.5 % Partial Load (75%) 89.2 % Partial Load (50%) 87.6 %
IP Class	IP55
Insulation Class	ICLF
Direction of Rotation	Both sides
Number of Poles (High)	2
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D

Mechanical

Frame Material	Aluminum
Frame Size	132
Bearing	6208-2Z/C3
Bearing NDE	6206-2Z/C3
IM Class	IMB14 IM3601
Terminator Box Location	D-End top

Dimensions

Package Level 1 Units	0 carton
Product Net Depth / Length	487 mm
Product Net Height	296 mm
Product Net Width	262 mm
Product Net Weight	52 kg
Gross Weight	57 kg

Environmental

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

SCIP27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)

Classifications

UNSPSC26101100

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors
Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

