




PRODUCT-DETAILS

3GAA131260-ADE

IE2 High Efficiency Aluminum Motors, 11 kW, 400 V (3GAA131260-ADE)



General Information

Product ID	3GAA131260-ADE
ABB Type Designation	M3AA 132SMF 2
Catalog Description	IE2 High Efficiency Aluminum Motors, 11 kW, 400 V (3GAA131260-ADE)

Ordering

ABB Type Designation	M3AA 132SMF 2
Invoice Description	M3AA 132SMF 2
Product Name	3-Phase squirrel cage motor
Product Type	3AA2_M3AA_IE2_AA
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	Poland (PL) Finland (FI) China (CN)
Customs Tariff Number	85015230
Replaced Product ID (OLD)	3GAA131063-ADA 3GAA131315-ADE
Stocked At (Warehouses)	Menden, Germany Vittuone, Italy
Medium Description	11kW, 2 Poles, Frame Size 132, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GAA131260-ADE)

Short Description11kW, 2P, Frame Size 132, 3PH, 400V, 50Hz, IP55, IMB3/IM1001

Electrical

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	11.00 kW	2900 r/min	11.40 A	0.870	90.30 %	36.20 N·m	8.50
D	--	50 Hz	400 V	11.00 kW	2900 r/min	20.20 A	0.870	90.30 %	36.20 N·m	8.50
D	--	60 Hz	460 V	11.00 kW	3504 r/min	17.20 A	0.940	90.90 %	30.00 N·m	9.00

Connection Configuration	D
Temperature Class	--
Default	
Input Voltage (U _{in})	400 V
Frequency (f)	50 Hz
Output Power	11 kW
Altitude	1000 m
Ambient Temperature	40 °C
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 90.3 % Partial Load (75%) 90.5 % Partial Load (50%) 89.4 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 90.9 % Partial Load (75%) 90.3 % Partial Load (50%) 88.3 %
IP Class	IP55
Insulation Class	ICLF
Direction of Rotation	Both sides
Number of Poles (High)	2
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D

Mechanical

Frame Material	Aluminum
Frame Size	132
Bearing	6308-2Z/C3
Bearing NDE	6206-2Z/C3
IM Class	IMB3 IM1001
Terminator Box Location	D-End top

Dimensions

Package Level 1 Units	0 carton
Product Net Depth / Length	487 mm
Product Net Height	296 mm
Product Net Width	262 mm
Product Net Weight	77 kg
Gross Weight	82 kg

Environmental

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

SCIP27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)

Classifications

UNSPSC26101100

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

