




PRODUCT-DETAILS

3GAA132360-ADE

IE2 High Efficiency Aluminum Motors, 9.2 kW, 400 V (3GAA132360-ADE)



General Information

Product ID	3GAA132360-ADE
ABB Type Designation	M3AA 132MF 4
Catalog Description	IE2 High Efficiency Aluminum Motors, 9.2 kW, 400 V (3GAA132360-ADE)

Ordering

ABB Type Designation	M3AA 132MF 4
Invoice Description	M3AA 132MF 4
Product Name	3-Phase squirrel cage motor
Product Type	3AA2_M3AA_IE2_AA
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	Finland (FI) Poland (PL) China (CN)
Customs Tariff Number	85015230
Replaced Product ID (OLD)	3GAA132004-ADE
Stocked At (Warehouses)	Menden, Germany Vittuone, Italy
Medium Description	9.2kW, 4 Poles, Frame Size 132, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GAA132360-ADE)

Short Description9.2kW, 4P, Frame Size 132, 3PH, 400V, 50Hz, IP55, IMB3/IM1001

Electrical

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	9.20 kW	1460 r/min	10.80 A	0.790	89.80 %	60.10 N·m	7.30
D	--	50 Hz	400 V	9.20 kW	1460 r/min	18.70 A	0.790	89.80 %	60.10 N·m	7.30
D	--	60 Hz	460 V	9.20 kW	1765 r/min	16.00 A	0.790	91.30 %	49.70 N·m	8.30

Connection Configuration	D
Temperature Class	--
Default	
Input Voltage (U _{in})	400 V
Frequency (f)	50 Hz
Output Power	9.2 kW
Altitude	1000 m
Ambient Temperature	40 °C
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 89.8 % Partial Load (75%) 90.8 % Partial Load (50%) 90.2 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 91.3 % Partial Load (75%) 91.5 % Partial Load (50%) 90.2 %
IP Class	IP55
Insulation Class	ICLF
Direction of Rotation	Both sides
Number of Poles (High)	4
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D

Mechanical

Frame Material	Aluminum
Frame Size	132
Bearing	6208-2Z/C3
Bearing NDE	6206-2Z/C3
IM Class	IMB3 IM1001
Terminator Box Location	D-End top

Dimensions

Package Level 1 Units	0 carton
Product Net Depth / Length	487 mm
Product Net Height	296 mm
Product Net Width	262 mm
Product Net Weight	59 kg
Gross Weight	64 kg

Environmental

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

SCIP

27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)

Classifications

UNSPSC

26101100

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

