



PRODUCT-DETAILS

3GAA162420-ADK

IE3 Premium Efficiency Aluminum Motors, 15 kW, 400 V (3GAA162420-ADK)



General Information

Product ID	3GAA162420-ADK
ABB Type Designation	M3AA 160MLB 4
Catalog Description	IE3 Premium Efficiency Aluminum Motors, 15 kW, 400 V (3GAA162420-ADK)

Ordering

ABB Type Designation	M3AA 160MLB 4
Invoice Description	M3AA 160MLB 4
Product Name	3-Phase squirrel cage motor
Product Type	3AA3_M3AA_IE3_AA
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	Poland (PL) Finland (FI) China (CN)
Customs Tariff Number	85015230
Replaced Product ID (OLD)	3GAA162052-ADK
Stocked At (Warehouses)	Menden, Germany Sant Quirze del Vallés - BCN, Spain
Medium Description	15kW, 4 Poles, Frame Size 160, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GAA162420-ADK)

Short Description15kW, 4P, Frame Size 160, 3PH, 400V, 50Hz, IP55, IMB3/IM1001

Electrical

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	15.00 kW	1474 r/min	16.80 A	0.810	92.10 %	97.19 N·m	7.80
D	--	50 Hz	400 V	15.00 kW	1474 r/min	29.00 A	0.810	92.10 %	97.15 N·m	7.80
Y	--	50 Hz	660 V	15.00 kW	1470 r/min	17.30 A	0.820	92.10 %	97.43 N·m	7.10
D	--	50 Hz	380 V	15.00 kW	1470 r/min	30.10 A	0.820	92.10 %	97.44 N·m	7.10
D	--	50 Hz	415 V	15.00 kW	1476 r/min	28.60 A	0.790	92.10 %	97.02 N·m	8.40
D	--	60 Hz	460 V	15.00 kW	1777 r/min	25.70 A	0.790	93.00 %	80.59 N·m	8.90

Connection Configuration	D
Temperature Class Default	--
Input Voltage (U _{in})	400 V
Frequency (f)	50 Hz
Output Power	15 kW
Altitude	1000 m
Ambient Temperature	40 °C
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 92.1 % Partial Load (75%) 92.0 % Partial Load (50%) 90.9 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 93.0 % Partial Load (75%) 92.6 % Partial Load (50%) 91.2 %
IP Class	IP55
Insulation Class	ICLF
Direction of Rotation	Both sides
Number of Poles (High)	4
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D

Mechanical

Frame Material	Aluminum
Frame Size	160
Bearing	6309-2Z/C3
Bearing NDE	6209-2Z/C3
IM Class	IMB3 IM1001
Terminator Box Location	D-End top

Dimensions

Package Level 1 Units	0 pallet (lift)
Product Net Depth / Length	681 mm
Product Net Height	370 mm
Product Net Width	310 mm
Product Net Weight	140 kg
Gross Weight	150 kg

Environmental	
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Classifications	
UNSPSC	26101100

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

