

PRODUCT-DETAILS

# 3GAA164420-BSK

## IE3 Premium Efficiency Aluminum Motors, 5.5 kW, 400 V (3GAA164420-BSK)



General Information	
Product ID	3GAA164420-BSK
ABB Type Designation	M3AA 160MLB 8
Catalog Description	IE3 Premium Efficiency Aluminum Motors, 5.5 kW, 400 V (3GAA164420-BSK)

Ordering	
ABB Type Designation	M3AA 160MLB 8
Invoice Description	M3AA 160MLB 8
Product Name	3-Phase squirrel cage motor
Product Type	3AA3_M3AA_IE3_AA
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	Finland (FI) China (CN)
Customs Tariff Number	85015220
Medium Description	5.5kW, 8 Poles, Frame Size 160, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GAA164420-BSK)
Short Description	5.5kW, 8P, Frame Size 160, 3PH, 400V, 50Hz, IP55, IMB5/IM3001

Electrical

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	5.50 kW	732 r/min	13.00 A	0.690	86.20 %	71.70 N·m	5.00
D	--	50 Hz	230 V	5.50 kW	732 r/min	22.50 A	0.690	86.20 %	71.70 N·m	5.00
Y	--	50 Hz	380 V	5.50 kW	730 r/min	13.20 A	0.720	86.20 %	71.90 N·m	4.60
D	--	50 Hz	220 V	5.50 kW	730 r/min	22.80 A	0.720	86.20 %	71.90 N·m	4.60
Y	--	50 Hz	415 V	5.50 kW	733 r/min	13.10 A	0.660	86.20 %	71.60 N·m	5.20
Y	--	60 Hz	460 V	5.50 kW	886 r/min	11.40 A	0.670	86.50 %	59.20 N·m	5.60

Connection Configuration	Y
Temperature Class Default	--
Input Voltage (U <sub>in</sub> )	400 V
Frequency (f)	50 Hz
Output Power	5.5 kW
Altitude	1000 m
Ambient Temperature	40 °C
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 86.2 % Partial Load (75%) 86.7 % Partial Load (50%) 85.2 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 86.5 % Partial Load (75%) 86.5 % Partial Load (50%) 84.6 %
IP Class	IP55
Insulation Class	ICLF
Direction of Rotation	Both sides
Number of Poles (High)	8
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S

Mechanical

Frame Material	Aluminum
Frame Size	160
Bearing	6309-2Z/C3
Bearing NDE	6209-2Z/C3
IM Class	IMB5 IM3001
Terminator Box Location	D-End top

Dimensions

Package Level 1 Units	0 pallet (lift)
Product Net Depth / Length	584 mm
Product Net Height	370 mm
Product Net Width	310 mm
Product Net Weight	96 kg

Gross Weight106 kg

Environmental

WEEE Category4. Large Equipment (Any External Dimension More Than 50 cm)  
SCIP27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)

Classifications

UNSPSC26101100

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

