



PRODUCT-DETAILS

3GAA181420-HDK

IE3 Premium Efficiency Aluminum Motors, 30 kW, 400 V (3GAA181420-HDK)



General Information

Product ID	3GAA181420-HDK
ABB Type Designation	M3AA 180MLB 2
Catalog Description	IE3 Premium Efficiency Aluminum Motors, 30 kW, 400 V (3GAA181420-HDK)

Ordering

ABB Type Designation	M3AA 180MLB 2
Invoice Description	M3AA 180MLB 2
Product Name	3-Phase squirrel cage motor
Product Type	3AA3_M3AA_IE3_AA
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Replaced Product ID (OLD)	3GAA181052-HDK
Medium Description	30kW, 2 Poles, Frame Size 180, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB35/IM2001 Mounting (3GAA181420-HDK)
Short Description	30kW, 2P, Frame Size 180, 3PH, 400V, 50Hz, IP55, IMB35/IM2001

Electrical

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	30.00 kW	2957 r/min	30.50 A	0.880	93.30 %	96.88 N·m	8.70
D	--	50 Hz	400 V	30.00 kW	2957 r/min	52.70 A	0.880	93.30 %	96.88 N·m	8.70
Y	--	50 Hz	660 V	30.00 kW	2951 r/min	31.60 A	0.890	93.30 %	97.08 N·m	7.90
D	--	50 Hz	380 V	30.00 kW	2951 r/min	54.80 A	0.890	93.30 %	97.08 N·m	7.90
D	--	50 Hz	415 V	30.00 kW	2960 r/min	52.00 A	0.860	93.30 %	96.78 N·m	9.20
D	--	60 Hz	460 V	30.00 kW	3563 r/min	45.70 A	0.880	93.30 %	80.40 N·m	10.00

Connection Configuration	D
Temperature Class	--
Default	
Input Voltage (U <sub>in</sub> )	400 V
Frequency (f)	50 Hz
Output Power	30 kW
Altitude	1000 m
Ambient Temperature	40 °C
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.3 % Partial Load (75%) 93.9 % Partial Load (50%) 93.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 93.3 % Partial Load (75%) 93.5 % Partial Load (50%) 92.9 %
IP Class	IP55
Insulation Class	ICLF
Direction of Rotation	Both sides
Number of Poles (High)	2
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D

Mechanical

Frame Material	Aluminum
Frame Size	180
Bearing	6310/C3
Bearing NDE	6209/C3
IM Class	IMB35 IM2001
Terminator Box Location	D-End top

Dimensions

Package Level 1 Units	0 pallet (lift)
Product Net Depth / Length	726 mm
Product Net Height	405 mm
Product Net Width	341 mm
Product Net Weight	162 kg
Gross Weight	172 kg

Environmental

WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
---------------	---

SCIP27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)

Classifications

UNSPSC26101100

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

