



PRODUCT-DETAILS

3GAA203420-ASG

IE2 High Efficiency Aluminum Motors, 22 kW, 400 V (3GAA203420-ASG)



General Information	
Product ID	3GAA203420-ASG
ABB Type Designation	M3AA 200MLB 6
Catalog Description	IE2 High Efficiency Aluminum Motors, 22 kW, 400 V (3GAA203420-ASG)

Ordering	
ABB Type Designation	M3AA 200MLB 6
Invoice Description	M3AA 200MLB 6
Product Name	3-Phase squirrel cage motor
Product Type	3AA2_M3AA_IE2_AA
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Replaced Product ID (OLD)	3GAA203062-ASA 3GAA203032-ASG
Medium Description	22kW, 6 Poles, Frame Size 200, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GAA203420-ASG)

Short Description

22kW, 6P, Frame Size 200, 3PH, 400V, 50Hz, IP55, IMB3/IM1001

Electrical

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	22.00 kW	987 r/min	42.00 A	0.820	92.00 %	212.00 N·m	6.60
D	--	50 Hz	230 V	22.00 kW	987 r/min	73.50 A	0.820	92.00 %	212.00 N·m	6.60
Y	--	50 Hz	415 V	22.00 kW	988 r/min	41.40 A	0.800	92.20 %	212.00 N·m	7.00
Y	--	60 Hz	440 V	22.00 kW	1187 r/min	37.50 A	0.830	92.50 %	176.00 N·m	6.90
Y	--	60 Hz	460 V	22.00 kW	1189 r/min	36.70 A	0.810	92.70 %	176.00 N·m	7.50

Connection Configuration	Y
Temperature Class Default	--
Input Voltage (U _{in})	400 V
Frequency (f)	50 Hz
Output Power	22 kW
Altitude	1000 m
Ambient Temperature	40 °C
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 92.0 % Partial Load (75%) 92.9 % Partial Load (50%) 92.8 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 92.5 % Partial Load (75%) 93.1 % Partial Load (50%) 92.4 %
IP Class	IP55
Insulation Class	ICLF
Direction of Rotation	Both sides
Number of Poles (High)	6
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S

Mechanical

Frame Material	Aluminum
Frame Size	200
Bearing	6312-2Z/C3
Bearing NDE	6210-2Z/C3
IM Class	IMB3 IM1001
Terminator Box Location	D-End top

Dimensions

Package Level 1 Units	0 pallet (lift)
-----------------------	-----------------

Product Net Depth / Length	821 mm
Product Net Height	532 mm
Product Net Width	386 mm
Product Net Weight	218 kg
Gross Weight	228 kg

Environmental	
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)

Classifications	
UNSPSC	26101100

Categories	
Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors	

