



PRODUCT-DETAILS

3GAA224210-BSG

IE2 High Efficiency Aluminum Motors, 18.5 kW, 400 V (3GAA224210-BSG)



General Information	
Product ID	3GAA224210-BSG
ABB Type Designation	M3AA 225SMA 8
Catalog Description	IE2 High Efficiency Aluminum Motors, 18.5 kW, 400 V (3GAA224210-BSG)

Ordering	
ABB Type Designation	M3AA 225SMA 8
Invoice Description	M3AA 225SMA 8
Product Name	3-Phase squirrel cage motor
Product Type	3AA2__M3AA_IE2_AA
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Replaced Product ID (OLD)	3GAA224061-BSA 3GAA224031-BSG
Medium Description	18.5kW, 8 Poles, Frame Size 225, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GAA224210-BSG)

Short Description

18.5kW, 8P, Frame Size 225, 3PH, 400V, 50Hz, IP55, IMB5/IM3001

Electrical

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	18.50 kW	739 r/min	40.10 A	0.730	90.00 %	239.00 N·m	5.20
D	--	50 Hz	230 V	18.50 kW	739 r/min	70.20 A	0.730	90.00 %	239.00 N·m	5.20
Y	--	50 Hz	415 V	18.50 kW	740 r/min	39.10 A	0.720	90.00 %	239.00 N·m	5.60
Y	--	60 Hz	440 V	18.50 kW	889 r/min	36.10 A	0.730	90.10 %	198.00 N·m	5.40
Y	--	60 Hz	460 V	18.50 kW	890 r/min	35.00 A	0.720	90.10 %	198.00 N·m	5.90

Connection Configuration	Y
Temperature Class Default	--
Input Voltage (U _{in})	400 V
Frequency (f)	50 Hz
Output Power	18.5 kW
Altitude	1000 m
Ambient Temperature	40 °C
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 90.0 % Partial Load (75%) 90.8 % Partial Load (50%) 90.0 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 90.1 % Partial Load (75%) 90.4 % Partial Load (50%) 89.1 %
IP Class	IP55
Insulation Class	ICLF
Direction of Rotation	Both sides
Number of Poles (High)	8
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S

Mechanical

Frame Material	Aluminum
Frame Size	225
Bearing	6313-2Z/C3
Bearing NDE	6212-2Z/C3
IM Class	IMB5 IM3001
Terminator Box Location	D-End top

Dimensions

Package Level 1 Units	0 pallet (lift)
-----------------------	-----------------

Product Net Depth / Length	850 mm
Product Net Height	547 mm
Product Net Width	425 mm
Product Net Weight	266 kg
Gross Weight	276 kg

Environmental

WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)

Classifications

UNSPSC	26101100
--------	----------

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

