



PRODUCT-DETAILS

# 3GBA092110-BSVCN

## No Description Available

General Information																																												
Product ID						3GBA092110-BSVCN																																						
ABB Type Designation						M2BAK90SA4																																						
Catalog Description						No Description Available																																						
Additional Information																																												
ABB Type Designation						M2BAK90SA4																																						
Altitude						1000 m																																						
Ambient Temperature						40 °C																																						
Bearing						6205-2Z/C3																																						
Bearing NDE						6205-2Z/C3																																						
Country of Origin						China (CN)																																						
Customs Tariff Number						85015100																																						
Direction of Rotation						Both sides																																						
Electrical Data																																												
<table><tr><th>Conn</th><th>Temp Class</th><th>Freq</th><th>Voltage</th><th>Power</th><th>Speed</th><th>Current</th><th>Power Factor</th><th>Efficiency</th><th>Torque</th><th>IS/IN</th></tr><tr><td>D</td><td>--</td><td>50 Hz</td><td>220 V</td><td>1.10 kW</td><td>1435 r/min</td><td>4.36 A</td><td>0.750</td><td>86.80 %</td><td>7.32 N·m</td><td>34.85</td></tr><tr><td>Y</td><td>--</td><td>50 Hz</td><td>380 V</td><td>1.10 kW</td><td>1435 r/min</td><td>2.52 A</td><td>0.750</td><td>86.80 %</td><td>7.32 N·m</td><td>20.15</td></tr></table>												Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN	D	--	50 Hz	220 V	1.10 kW	1435 r/min	4.36 A	0.750	86.80 %	7.32 N·m	34.85	Y	--	50 Hz	380 V	1.10 kW	1435 r/min	2.52 A	0.750	86.80 %	7.32 N·m	20.15
Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN																																		
D	--	50 Hz	220 V	1.10 kW	1435 r/min	4.36 A	0.750	86.80 %	7.32 N·m	34.85																																		
Y	--	50 Hz	380 V	1.10 kW	1435 r/min	2.52 A	0.750	86.80 %	7.32 N·m	20.15																																		
Frame Size						90																																						
Gross Weight						30 kg																																						
IC Class						IC411																																						
IE Class Data (50 Hz)						IE Class IE4 Full Load (100%) 87.2 % Partial Load (75%) 87.8 % Partial Load (50%) 86.8 %																																						
IE Class Data (60 Hz)						IE Class NA																																						
IM Class						IMB5 IM3001																																						
Insulation Class						ICLF																																						
IP Class						IP55																																						
Made To Order						No																																						
Minimum Order Quantity						1 piece																																						
Number of Poles (High)						4																																						

Order Multiple	1 piece
Product Name	3-Phase squirrel cage motor
Product Net Weight	30 kg
Product Type	CBK4__M2BAK_IE4_CI
Quote Only	No
Selling Unit of Measure	piece
Stocked At (Warehouses)	Shanghai, China Guangzhou, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S